

## Wind Energy – New Dimensions in Metrology

Thomas Wiedenhöfer, Frank Härtig

## Application of wind energy about 1500 BC




## sailing vessels in the ancient Egypt



photo: Elvira Kronlob

### windmills in China



source: Carl von Canstein

### Goals for wind energy systems (WES)



- Core environmental and sustainable objectives
  - reduction of greenhouse gases
  - avoidance of pollution / dangerous waste (coal / nuclear plants)
- Technical and economical objectives
  - competitiveness with conventional energy supply
  - reliability, safety, reasonable maintenance (lifetime 20 years)
- Political objectives
  - secure energy supply (at all weather conditions)
  - development of structured grids
  - reduction of subsidies and infrastructure costs


<u>Germany:</u> renewable energy sources act

2020 35% renewable energy; (today 25%)

### **Development and forecast of WES sizes**




In less than 30 years, the yield from wind turbines has increased more than 500 times



### Components of the WES drive train








source: Bosch-Rexroth


## Failure frequencies and impacts





source: Fraunhofer IWES, Kassel

## Cost distribution caused by WES failures '09 PB



source: Sensen, Gothaer Allgemeine Versicherung AG

### Traceability of dimensional and torque measurement



#### Biggest systems in dimensional metrology:

PTB / NPL / NMIJ, ...: measuring volume < 1m<sup>3</sup>

<u>problem:</u> no standards > 1m<sup>3</sup> available worldwide

#### **Calibration of torque**

PTB: 1100 kN·m (biggest system worldwide)

Himmelstein (USA): 450 kN·m


SMERI (China): 200 kN·m (biggest system with direct mass)

LNE (Frankreich): 200 kN·m

problem: systems traceable only up to 1100 kN·m

### **Competence Centre "Wind Energy"**






### Calibration for gear measurement today



- measurements in industry
- mover: CMM
- environment: measuring room
- workpiece: calibrated involute gear artefact (reference, validation)

Parameter	Value
Number of teeth z	38
Normal module $m_n$	20 mm
Pressure angle $\alpha_n$	20°
Face width b	400 mm
Helix angle	0°/spur; 10°/R; 20°/L
Outside diameter d <sub>a</sub>	1000 mm
Weight	450 kg (700 kg)
Reference bands diameter (form deviation)	200 mm (1 μm)






# Concept for precise coordinate measurement of big work pieces 1/4



#### 1<sup>st</sup> step – real measurement

- measure workpieceuse CMM and application software
- register spatial locationsin machine coordinates (x, y, z)
- export of all probing pointsfrom the application program



Cartesian CMM (not Abbe error free)

# Concept for precise coordinate measurement of big work pieces 2/4



### 2<sup>nd</sup> step – 3D-Abbe measurement

- remove workpiece
- exchange stylus by triple reflector approximately at same centres




Cat-Eye working range 120°



n=2-ball working range 160°



- move to all measurement points measured in step 1
- synchronised read out of all tracking interferometer




3D Abbe error free measurement for measurements on Cartesian CMMs

# Concept for precise coordinate measurement of big work pieces 3/4



3<sup>rd</sup> step – evaluate the local error vector and correct mover points



# Concept for precise coordinate measurement of big work pieces 4/4






## Calibration of torque 5 MNm to 20 MNm




part under test



### Third part of CC-Wind: Wind-Lidar





conventional LIDAR

new – LIDAR calibration system

to be calibrated

Measurement height: 10m - 200m

measuring mast free


MU: 0,1 m/s; spatial resolution: 10<sup>-9</sup> m<sup>3</sup>

### Clues for further development and needs







#### Total Installed Capacity 2011-2015 [MW]



\* Estimated
Total installed capacity: Includes all installed wind capacity, connected and not-connected to the grid.



installierte Leistung [GW]



### Thank you for your kind attention



## Physikalisch-Technische Bundesanstalt Braunschweig and Berlin

Bundesallee 100 38116 Braunschweig

Thomas Wiedenhöfer (Wiedenhoefer)

Telefon: +49 (0)531 592-1189

E-Mail: thomas.wiedenhoefer@ptb.de

www.ptb.de